

Site Lighting

LED Non-Corrosive Fittings



- Dual Voltage 110V-240V.
- Supplied with integrated LED Tray.
- Daylight (5500k).
- High quality polycarbonate base and diffuser.
- Includes mounting brackets and polycarbonate clips.
- 100lm/W.
- IP65.
- Emergency fittings 3 hour run time.

Part No.	Wattage	Description
TRLED8010	20W	2ft Standard
TRLED8011	20W	2ft Emergency
TRLED8020	30W	5ft Standard
TRLED8021	30W	5ft Emergency
TRLED8015	40W	4ft Standard
TRLED8016	40W	4ft Emergency
TRLED8240	40W	5ft Standard
TRLED8241	40W	5ft Emergency

LED Plasterer Lights



- Site yellow polycarbonate body.
- Opal diffuser for an even spread of light.
- Metal frame.
- Supplied with fitted 16A 110V plug.
- Integrated driver.
- 2 x 16A 110V sockets on frame.
- Supplied with 5m of cable.
- 6300K Colour Temp.
- IP65.

Part No.	Wattage	Lumens	Description
P1000	20W	2000lm	2ft A-Frame
P1010	20W	2000lm	2ft Plasterers Light
P1020	30W	2500lm	5ft Plasterers Light

King Cobra 110V Tasklight



- Super bright LED.
- Durable aluminium die-cast housing & tempered glass diffuser.
- Rotate and swivel function.
- Single or twin head functions.
- 100° beam angle
- 75lm/W.
- 20,000 hours rated life.

Part No.	Wattage	Description	Plug	Lumens
S3100	10W	Single + Tripod	16A	1500lm
S3110	2x20W	Twin + Tripod	16A	2x1500lm
S3120	2x20W	Twin Upgrade Kit	16A	2x1500lm

King Cobra Rechargeable Tasklight



- Super bright LED - Daylight (5500K).
- Durable aluminium die-cast housing & tempered glass diffuser.
- Rotate and swivel function.
- Single or twin head functions.
- Supplied with mains charger.
- 100° beam angle.
- 75lm/W.
- 20,000 hours rated life.

Part No.	Wattage	Description	Work Time	Lumens
S3200	8W	Single + Tripod	3hr	600lm
S3210	2x8W	Twin + Tripod	3hr	2x600lm
S3220	2x8W	Twin Upgrade Kit	3hr	2x600lm

Cobra 110V Tasklight



- Super bright LED - Daylight (5500K).
- Durable aluminium die-cast housing.
- Tempered glass diffuser.
- Rotate and swivel function.
- Single or twin head options.
- 100° beam angle.
- 75lm/W.
- 20,000 hours rated life.

Part No.	Wattage	Description	Plug	Lumens
S3050	10W	Single	13A	750lm
S3070	2x10W	Twin	13A	2x750lm
S3080	2x20W	Twin	13A	2x1500lm

Brackenheath



Cobra Rechargeable Tasklight



- Super bright LED - Daylight (5500K).
- Durable aluminium die-cast housing & tempered glass diffuser.
- Rotate and swivel function.
- Single or twin head functions.
- Supplied with mains charger.
- 100° beam angle.
- 75lm/W.
- 20,000 hours rated life.

Part No.	Wattage	Description	Work Time	Lumens
S3150	8W	Single	3hr	600lm
S3170	2x8W	Twin	3hr	2x600lm
S3160	18W	Single	3hr	1200lm
S3180	2x18W	Twin	3hr	2x1200lm

Festoon Kits



- Complete 25m festoon kit includes 10 guards and lamps.
- Arctic grade 2.5mm cable.
- BC or ES lampholders.
- Lampholders spaced every 2m.
- 5m lead includes 16A plug.
- IP44.
- 110V.

Part No.	Wattage	Lamp Base	Cable Length	Lamp Type
SEFLLEDBC	8W	BC	25m	LED GLS
SEFLLEDES	8W	ES	25m	LED GLS
SEFLKITBC	60W	BC	25m	GLS
SEFLKITES	60W	ES	25m	GLS

Festoon Cables



- Festoon Cable in 100m length.
- Arctic grade 2.5mm cable.
- BC or ES lampholders.
- Lampholders spacing between 2-3m.
- IP44.
- 110V.

Part No.	Wattage	Lamp Base	Cable Length	No. of Lampholders
SEFL13E	60W Max	ES	100m	33
SEFL13B	60W Max	BC	100m	33

Lighting & Transformers

LED Task Lights



- Super Bright LED - Daylight.
- Die cast aluminium body with polycarbonate diffuser.
- Protective rubber trim.
- Foldaway ABS stand with carry handle.
- On/off switch on rear.

Part No.	Wattage	Lumens	Finish
S2010	36W	2400lm	Yellow
S2030	20W	1400lm	Green

LED Brick Bulkheads



- Dual voltage 110V - 230V.
- Aluminium base.
- Polycarbonate diffuser.
- Red or opal diffuser options.
- Integrated LED Chip Tray.
- 20mm conduit entry point.
- Suitable for mounting on BESA box.
- IP65.

Part No.	Wattage	Finish
B2010	8W	Opal Diffuser
B2020	8W	Red Diffuser

Site Extension Leads



Cable Reels

- Heavy duty tubular steel frame with carry handle.
- Two 16A outlet sockets.
- 25m cable length.
- 1.5mm cable thickness.

Extension Leads

- Extension leads utilise arctic cable.
- Fitted with plug and coupler.
- 14m cable length.
- Available with 1.5mm & 2.5mm cable thickness.
- IP44.

Part No.	Description	Voltage	Cable Size	Plug Rating
SE1010	10m Cassette	100-130V	1.25mm	16A
SE1020	15m Handbag	100-130V	1.25mm	16A
SE1030	25m Open Reel	100-130V	1.25mm	16A
SE1040	50m Open Reel	100-130V	1.25mm	16A
SE2010	25m O/Reel / 2 USB	220-240V	1.25mm	13A
SE2020	25m O/Reel / 2 USB	100-130V	1.25mm	16A
SE3010	14m Yellow	100-130V	1.5mm	16A
SE3020	14m Blue	220-240V	1.5mm	13A
SE3030	14m Yellow	100-130V	2.5mm	16A
SE3040	14m Blue	220-240V	2.5mm	13A
SE3050	25m Yellow H Frame	100-130V	1.5mm	16A
SE3060	25m Blue H Frame	220-240V	1.5mm	13A
SE3070	25m Yellow H Frame	100-130V	2.5mm	16A
SE3080	25m Blue H Frame	220-240V	2.5mm	13A
SE3090	14m Yellow H Frame	100-130V	2.5mm	32A
SE3100	14m Blue H Frame	220-240V	2.5mm	32A
SE3110	25m Yellow H Frame	100-130V	2.5mm	32A
SE3120	25m Blue H Frame	220-240V	2.5mm	32A

Portable Site Transformers



- Robust GRP case with carry handle.
- Step down from 230V to 110V CTE supply.
- Resettable thermal cut out.
- Supplied complete with 2m cable and 13A plug.
- IP44.

Part No.	Continuous Rating	Weight	Socket Outlets
1000/2/b	0.6kVA	12.5kg	2x16A
1500/2/b	0.9kVA	13kg	2x16A
3300/2/b	2.2kVA	17kg	2x16A
5000/3/b	2.8kVA	29kg	2x16A, 1x32A

Site Supply Transformers



- Heavy duty steel enclosure.
- Three phase 415V and single phase 230V input options.
- Step down to 110V CTE supply.
- IP44.
- Hard wired input.
- 16A and 32A socket outlets.
- MCB protected inout and output.
- 25mm conduit entries on both sides.

Part No.	Continuous Rating	Weight	Socket Outlets
10000/1PH	10kVA	61kg	4x16A, 2x32A
10000/3PH	10kVA	78kg	4x16A, 2x32A